



. . . c o n n e c t i n g   y o u r   b u s i n e s s

## LANCOM IAP-54 Wireless

### Dual-band access point for tough environments

- Rugged dualband access point for 2.4 or 5 GHz frequencies with 54/108 Mbps with IEEE 802.11a/b/g/h
- Robust metal housing with IP50 dust protection, ready for wall, top-hat rail, or pole mounting; for deployment in warehouses, production facilities and similar environments
- No-problems installation even away from power-supply points with Power-over-Ethernet (1-port LANCOM PoE Power Injector included; not applicable to bulk version)
- Secure wireless LAN through IEEE 802.11i, IEEE 802.1x/EAP, LEPS, with AES encryption in hardware
- Secure Internet access via the integrated DSL router with stateful inspection firewall with intrusion detection/denial-of-service protection
- Separation of user groups by Multi-SSID and VLAN

With an IP50-standard dust-resistant metal housing, the LANCOM IAP-54 Wireless industrial access point has been especially designed for use in warehouses, production facilities and other demanding sites outside of the clean office environment.

Three different mounting options—wall, pole, or top-hat rail—and the Power-over-Ethernet power supply meet the toughest of requirements and mean that the LANCOM IAP-54 Wireless can be deployed just about anywhere.

The LANCOM IAP-54 Wireless also offering considerable flexibility with its 108-Mbps wireless module compliant with IEEE 802.11a/b/g/h and two dualband diversity antennas. Depending upon requirements, the access point can be operated in the 2.4-GHz frequency range and at 5 GHz.

#### **More Security.**

LANCOM sets the standards in WLAN security. A comprehensive range of security technologies is supported in wireless LAN including IEEE 802.11i, 802.1x, WPA, WPA2, WEP64/128/152, access control lists or LEPS (LANCOM Enhanced Passphrase Security), which enables the configuration of an optimized solution, whatever the individual requirements. For example, Multi SSID allows the definition of up to 8 user groups, each with its own level of security.

#### **More Management.**

LANCOM developments are focused on performance, security and on management, too. LANCOM's WLAN management tools offer real benefits to network administrators for the installation, control and monitoring of access points. Settings for wireless, encryption, or access control lists can be grouped into partial configurations, which are then executed for multiple access points in one easy move. A group configuration is assigned to a group folder and the changes are automatically sent to all of the devices. Adding in new devices? Simply add them to the group folder by drag and drop. Different settings? WLAN group configuration offers an automatic update. WLANmonitor visualizes the structures of the WLAN irrespective of physical location and facilitates the central surveillance of the entire wireless network.

#### **More Certainty for the Future.**

From the very start, LANCOM products are designed for a product life of several years. They are equipped with hardware dimensioned for the future. Even reaching back to older product generations, updates to the LANCOM Operating System—LCOS—are available several times a year, free of charge and offering major features. LANCOM offers unbeatable protection of your investment!

#### **More Independence.**

One cable is all you need. The access point takes its power supply from the LAN cable (Power-over-Ethernet), and it can be operated up to 60 m away from the nearest power socket.

Power is fed into the LAN at a central location by using a PoE injector or a power hub or power switch. The retail version of LANCOM IAP-54 Wireless is supplied with the required 1-port Power-over-Ethernet Injector as standard.

#### **What's more...**

To complete the WLAN portfolio, LANCOM also offers suitable AirLancer client adapters and a large selection of high-end antennas for professional indoor and outdoor applications.

# LANCOM IAP-54 Wireless

<b>Firewall</b>	
Stateful inspection firewall	Incoming/Outgoing Traffic inspection based on connection information
Packet filter	Check based on the header information of an IP packet (IP or MAC source/destination addresses; source/destination ports, DiffServ attribute); remote-site dependant, direction dependant, bandwidth dependant
Extended port forwarding	Network Address Translation (NAT) based on protocol and WAN address, i.e. to make internal webservers accessible from WAN
N:N IP address mapping	N:N IP address mapping for translation of IP addresses or entire networks
Tagging	The firewall marks packets with routing tags, e.g. for policy-based routing
Actions	Forward, drop, reject, block sender address, close destination port, disconnect
Notification	Via e-mail, SYSLOG or SNMP trap
<b>Quality of Service</b>	
Traffic shaping	Dynamic bandwidth management with IP traffic shaping
Bandwidth reservation	Dynamic reservation of minimum and maximum bandwidths, totally or connection bases, separate settings for send and receive directions
DiffServ/TOS	Priority queuing of packets based on DiffServ/TOS fields
Packet-size control	Automatic packet-size control by fragmentation or Path Maximum Transmission Unit (PMTU) adjustment.
Layer 2/Layer 3 tagging	Automatic or fixed translation of layer-2 priority information (802.11p-marked Ethernet frames) to layer-3 DiffServ attributes in routing mode. Translation from layer 3 to layer 2 with automatic recognition of 802.1p-support in the destination device.
<b>Security</b>	
Intrusion Prevention	Monitoring and blocking of login attempts and port scans
IP spoofing	Source IP address check on all interfaces: only IP addresses belonging to the defined IP networks are allowed
Access control lists	Filtering of IP or MAC addresses and preset protocols for configuration access
Denial of Service protection	Protection from fragmentation errors and SYN flooding
General	Detailed settings for handling reassembly, PING, stealth mode and AUTH port
URL blocker	Filtering of unwanted URLs based on DNS hitlists and wildcard filters
Password protection	Password-protected configuration access can be set for each interface
Alerts	Alerts via e-mail, SNMP-Traps and SYSLOG
Authentication mechanisms	EAP-TLS, EAP-TTLS, PEAP, MSCHAP, MXCHAPv2 as EAP authentication mechanisms, PAP, CHAP and MS-CHAP as PPP authentication mechanisms
WLAN protocol filters	Limitation of the allowed transfer protocols, source and target addresses on the WLAN interface
Adjustable reset button	Adjustable reset button for "ignore", "boot-only" and "reset-or-boot"
IP redirect	Fixed redirection of any packet received over the WLAN interface to a dedicated target address
<b>High availability / redundancy</b>	
VRRP	VRRP (Virtual Router Redundancy Protocol) for backup in case of failure of a device or remote station. Enables passive standby groups or reciprocal backup between multiple active devices including load balancing and user definable backup priorities
FirmSafe	For completely safe software upgrades thanks to two stored firmware versions, incl. test mode for firmware updates
Analog/GSM modem backup	Optional operation of an analog or GSM modem at the serial interface
Line monitoring	Line monitoring with LCP echo monitoring, up to 4 addresses for end-to-end monitoring with ICMP polling.
<b>WLAN</b>	
Frequency band 2.4 GHz or 5 GHz (EU compliance)	2400 - 2483.5 MHz (ISM) or 5150 - 5750 MHz or 5725-5825 MHz (UK only)
Transfer rates 2.4 GHz	54 Mbps to IEEE 802.11g (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection) compatible to IEEE 802.11b (11, 5.5, 2, 1 Mbps, Automatic Rate Selection), 802.11 b/g compatibility mode or pure g or pure b, Super A/G with Turbo Mode (108 Mbps), bursting, compression
Transfer rates 5 GHz	54 Mbps to IEEE 802.11a/h (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), Super A/G with Turbo Mode (108 Mbps), bursting, compression, fully compatible with TPC (adjustable power output) and DFS (automatic channel selection, radar detection) according to ETSI regulations
Range *	Up to 150 m (up to 30 m in buildings) *
Maximum transmission power 2.4 GHz	802.11b: +19 dBm @ 1 and 2 Mbps, +19 dBm @ 5.5 and 11 Mbps
Maximum transmission power 2.4 GHz	802.11g: +19 dBm @ 6 Mbps, +14 dBm @ 54 Mbps
Maximum transmission power 5 GHz	802.11a/h: +18 dBm @ 6 Mbps, +12 dBm @ 54 Mbps with transmission power control (TPC) and manual power settings
Minimum transmission power	Transmission power reduction in software in 1 dB steps to min. 0.5 dBm
Reception sensitivity 2.4 GHz	802.11b: -87 dBm @ 11 Mbps, -94 dBm @ 1 Mbps

# LANCOM IAP-54 Wireless

WLAN	
Reception sensitivity 2.4 GHz	802.11g: -87 dBm @ 6 Mbps, -70 dBm @ 54 Mbps
Reception sensitivity 5 GHz	802.11a/h: -87 dBm @ 6 Mbps, -67 dBm @ 54 Mbps
Radio channels 2.4 GHz	Up to 13 channels, max. 3 non-overlapping (2.4 GHz band)
Radio channels 5 GHz	Up to 19 non-overlapping channels (5 GHz band) with automatic dynamic channel selection (DFS)
Roaming	Seamless handover between radio cells, IAPP support, IEEE 802.11d support
802.11i fast roaming	Pre-authentication and PMK caching for fast roaming
Fast client roaming	With background scanning, moving LANCOM "client mode" Access Points pre-authenticate to alternative access points which offer a better signal before Roaming
VLAN	VLAN ID definable per interface, WLAN SSID, point-to-point connection and routing context (4094 IDs)
Dynamic VLAN assignment	Dynamic VLAN assignment for target user groups based on MAC addresses, BSSID or SSID by means of external RADIUS server.
Q-in-Q tagging	Support of layered 802.1q VLANs
Multi-SSID	Simultaneous use of up to 8 independent WLAN networks per WLAN interface
Security	IEEE 802.11i / WPA2 with passphrase or 802.1x and hardware-accelerated AES, closed network, WEP64, WEP128, WEP152, user authentication, 802.1x /EAP
RADIUS server	Integrated RADIUS server for MAC address list management
EAP server	Integrated EAP server for authentication of 802.1x clients via EAP-TLS, EAP-TTLS, PEAP, MSCHAP or MSCHAPv2
Quality of Service	Prioritization according to Wireless Multimedia Extensions (WME, subset of IEEE 802.11e)
Bandwidth limitation	Each WLAN client (MAC address) can be assigned maximum transmit and receive rates and to an individual VLAN ID
Background scanning	Detection of rogue AP's and the channel information for all WLAN channels during normal AP operation.
Client detection	Rogue WLAN client detection based on probe requests
802.1x supplicant	Authentication of an Access Point in WLAN client mode at another Access Point via 802.1X (EAP-TLS, EAP-TTLS and PEAP)
Note	* The effective distance and transmission rate that can be achieved are depending of the site RF conditions.
WLAN operating modes	
WLAN access point	Infrastructure mode (autonomous operation or managed by LANCOM WLAN Controller)
WLAN bridge	Point-to-multipoint connection of up to 7 Ethernet LANs (mixed operation optional), broken link detection, blind mode, up to 32 VLANs simultaneously for WLAN connections
WLAN router	Use of the LAN connector for simultaneous DSL over LAN, IP router, NAT/Reverse NAT (IP masquerading) DHCP server, DHCP client, DHCP relay server, DNS server, PPPoE client (incl. Multi-PPPoE), PPTP client and server, NetBIOS proxy, DynDNS client, NTP, port mapping, policy-based routing based on routing tags, tagging based on firewall rules, dynamic routing with RIPv2, VRRP, spanning-tree protocol to support redundant routes in Ethernet networks
WLAN client	Transparent WLAN client mode for wireless Ethernet extensions, e.g. connecting PCs or printers by Ethernet; up to 64 MAC addresses
Routing functions	
Router	IP and NetBIOS/IP multi-protocol router
Advanced Routing and Forwarding	Separate processing of 8 contexts due to virtualization of the routers. Mapping to VLANs and complete independent management and configuration of IP networks in the device, i.e. individual settings for DHCP, DNS, Firewalling, QoS, Routing etc.
HTTP	HTTP and HTTPS server for configuration by web interface
DNS	DNS client, DNS server, DNS relay, DNS proxy and dynamic DNS client
DHCP	DHCP client, DHCP relay and DHCP server with autodetection
NetBIOS	NetBIOS/IP proxy
NTP	NTP client and SNTP server, automatic adjustment for daylight-saving time
Policy-based routing	Policy-based routing based on routing tags. Based on firewall rules, certain data types are marked for specific routing, e.g. to particular remote sites or lines.
Dynamic routing	Dynamic routing with RIPv2. Learning and propagating routes; separate settings for LAN and WAN
Rapid Spanning Tree	802.1d Spanning Tree and 802.1w Rapid Spanning Tree support for dynamic path selection with redundant layer 2 connections
LAN protocols	
IP	ARP, proxy ARP, BOOTP, DHCP, DNS, HTTP, HTTPS, IP, ICMP, NTP/SNTP, NetBIOS, PPPoE (server), RADIUS, RIP-1, RIP-2, RTP, SIP, SNMP, TCP, TFTP, UDP, VRRP
WLAN protocols	
Ethernet	PPPoE, Multi-PPPoE, ML-PPP, PPTP (PAC or PNS) and plain Ethernet (with or without DHCP), RIP-1, RIP-2

# LANCOM IAP-54 Wireless

<b>Interfaces</b>	
LAN	10/100Base-TX, autosensing, auto node hub, PoE compliant with IEEE 802.3af
DSL over LAN (DSLolL)	The LAN port can (even parallel to LAN mode) be used as a WAN port for connecting external DSL modems (PPPoE) or external routers.
Serial interface	Serial configuration interface / COM port (8 pin Mini-DIN): 9,600 - 115,000 baud, suitable for optional connection of analog/GPRS modems
External antenna connectors	Two reverse SMA connectors for external LANCOM AirLancer Extender antennas or for antennas from other vendors. Please respect the restrictions which apply in your country when setting up an antenna system. For information about calculating the correct antenna setup, please refer to <a href="http://www.lancom-systems.com">www.lancom-systems.com</a> .
<b>Management</b>	
LANconfig	Configuration program for Microsoft Windows, incl. convenient Setup Wizards. Optional group configuration, simultaneous remote configuration and management of multiple devices over IP connection (HTTPS, HTTP, TFTP)
LANmonitor	Monitoring application for Microsoft Windows for (remote) surveillance and logging of the status of LANCOM devices and connections, incl. PING diagnosis
WLANmonitor	Monitoring application for Microsoft Windows for the visualization and monitoring of LANCOM WLAN installations, incl. Rogue AP and Rogue Client visualization
Webconfig	Integrated web server for the configuration of LANCOM devices via Internet browsers with HTTPS or HTTP
Access rights	Individual access and function rights for up to 16 administrators
User administration	RADIUS user administration for dial-in access (PPP/PPTP)
Remote maintenance	Remote configuration with Telnet/SSL, SSH (with password or public key), browser (HTTP/HTTPS), TFTP or SNMP, firmware upload via HTTP/HTTPS or TFTP. A remote configuration for devices behind der LANCOM can be accomplished (after authentication) via tunneling of arbitrary TCP-based protocols, e.g. for HTTP(S) remote maintenance of VoIP phones or printers of the LAN
Security	Access rights (read/Write) over WAN or (W)LAN can be set up separately (Telnet/SSL, SSH, SNMP, HTTPS/HTTP), access control list
Scripting	Scripting function for batch-programming of all command-line parameters and for transferring (partial) configurations, irrespective of software versions and device types, incl. test mode for parameter changes
SNMP	SNMP management via SNMP V2, private MIB exportable by WEBconfig, MIB II
Timed control	Scheduled control of parameters and actions with CRON service
TFTP	TFTP client and server with variable file names (name, MAC/IP address, serial number)
Diagnosis	Extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, LANmonitor status display, internal logging buffer for SYSLOG and firewall events, monitor mode for Ethernet ports
AirWave	On Request: Supported by the LANCOM Enterprise Management System (AirWave AMP, Site Planner, RAPIDS, Client)
<b>Statistics</b>	
Statistics	Extensive Ethernet, IP and DNS statistics; SYSLOG error counter
Accounting	Connection time, online time, transfer volumes per station. Snapshot function for regular read-out of values at the end of a billing period.
Export	Accounting information exportable via LANmonitor and SYSLOG
<b>Hardware</b>	
Power supply	12 V AC, external power adapter (230 V)
Power supply	Via Power over Ethernet, compliant with IEEE 802.3af, 1 x PoE Injector supplied
Environment	Temperature range 0–50 °humidity 0–95 %; non-condensing
Housing	225 mm x 152 mm x 45 mm (W x H x D), robust metal housing, IP 50 protection rating, including mounting material for wall, mast and top-hat rail mounting
Power consumption (max)	ca. 4.5 Watts
<b>Declarations of conformity</b>	
CE	EN 55022, EN 301 489-1, EN 301 489-17, EN 60950
2.4 GHz WLAN	ETS 300 328
5 GHz WLAN	EN 301 893
Medical	Medical conformity with EN 60601-1-2
Notifications	Certifications notified in Germany, Belgium, Netherlands, Luxembourg, Austria, Switzerland, UK, Italy, Spain, France, Portugal, Czech Republic, Denmark
<b>Package content</b>	
Manual	Printed User Manual (DE, EN) and Quick Installation Guide (DE/EN/FR/ES/IT/PT/NL)
CD	CD with firmware, management software (LANconfig, LANmonitor, WLANmonitor) and documentation
Cable	1 Ethernet cable, 3m

# LANCOM IAP-54 Wireless

Package content	
Antennas	Two 3 dBi dipole dualband antennas
Power supply unit	12 V AC, external power adapter (230 V)
Power supply unit	Via Power over Ethernet compliant with IEEE 802.3af, 1 x PoE Injector supplied
Support	
Warranty	3 years, support via Hotline and Internet KnowledgeBase
Software updates	Regular free updates (LCOS operating system and management tools) via Internet
Options	
Service	LANCOM Service Option (24h advance replacement within Germany, 4 year warranty, not for PoE Power Injector), item no. 61401
Public Spot	LANCOM Public Spot Option (authentication and accounting software for hotspots), item no. 60642
Accessories	
External antenna	AirLancer Extender O-30 2.4 GHz outdoor antenna, item no. 60478
External antenna	AirLancer Extender O-70 2.4 GHz outdoor antenna, item no. 60469
External antenna	AirLancer Extender O-9a 5 GHz outdoor antenna, item no. 61220
External antenna	AirLancer Extender O-18a 5 GHz outdoor antenna, item no. 61210
External antenna	AirLancer Extender O-D80g 2.4 GHz polarization diversity outdoor sector antenna, item no. 61221
External antenna	AirLancer Extender O-D60a 5 GHz polarization diversity outdoor sector antenna, item no. 61222
External antenna	AirLancer Extender O-360ag dualband omnidirectional outdoor antenna, item no. 61223
External antenna	AirLancer Extender I-60ag dualband indoor sector antenna, item no. 61214
External antenna	AirLancer Extender I-180 omnidirectional 2.4 GHz indoor antenna, item no. 60914
External antenna	AirLancer Extender I-360 omnidirectional 2.4 GHz indoor antenna, item no. 00745
Antenna cable	AirLancer cable NJ-NP 3m antenna-cable extension, item no. 61230
Antenna cable	AirLancer cable NJ-NP 6m antenna-cable extension, item no. 61231
Antenna cable	AirLancer cable NJ-NP 9m antenna-cable extension, item no. 61232
Lightning Protection (antenna cable)	AirLancer Extender SA-5 lightning protection (2.4 and 5 GHz), item no. 61212
Lightning Protection (LAN cable)	AirLancer Extender SA-LAN lightning protection LAN cable, item no. 61213
Documentation	LANCOM LCOS Reference Manual (DE), item no. 61700
Item numbers	
LANCOM IAP-54 Wireless	61504
LANCOM IAP-54 Wireless UK	61505
LANCOM IAP-54 Wireless (w/o Power Injector) 5-piece bulk	61506

LANCOM, LANCOM Systems and LCOS are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. Subject to change without notice. No liability for technical errors and/or omissions. 08/07