



. . . c o n n e c t i n g y o u r b u s i n e s s

LANCOM XAP-40-2

Industrial access point for automation and control

- High availability and WLAN redundancy through two radio modules
- 5-fold redundant power supply
- Access point and access client in one device
- Compact for space-saving top-hat rail mounting
- Maximum security from IEEE 802.11i, authentication and LEPS
- Built-in IP router and firewall
- VLAN and multiSSID separate user groups
- 2.4 and 5 GHz

The industrial access point LANCOM XAP-40-2 meets all of the demands that industrial settings place on wireless LAN. It features a robust metal housing which is suitable for top-hat rail or wall mounting. It is equipped to ensure high availability and redundancy and includes dual LAN ports which can both be fed by Power over Ethernet (IEEE 802.3af). Three further power sources can be used as well: 12V DC and two-times 24V DC. Operational reliability is assured over an extended temperature range of -20 °to +50 °which, being achieved without the use of a heater, ensures that power consumption is low.

Each WLAN module has two RP-SMA antenna connectors which are suitable for any of the LANCOM Systems range of AirLancer Extender antennas. This range of products includes polarization diversity antennas which ensure stable connections in industrial settings.

More flexibility.

Two integrated wireless-LAN modules can be set to 2.4 GHz (802.11b/g) or 5 GHz (802.11a/h) and offer you the full range of options in setting up wireless LAN networks. High availability is achieved by using the WLAN modules redundantly. These can also be used for WLAN relay or in a WDS (Wireless Distribution System).

More Security.

Maximum security is guaranteed by the integrated firewall and the full range of protective mechanisms for WLAN, including IEEE 802.11i with IEEE 802.1x authentication, WLAN filters and LEPS. Further features are fast roaming, rogue AP detection, and QoS compliant with IEEE 802.11e, all of which satisfy the very latest demands of wireless LANs.

More Management.

A network management system is included with the package. It has all of the features necessary for operating a professional network, including functions for commissioning, configuring and managing an access point, and rogue AP detection. In addition to that, the LANCOM Enterprise Management System provides a server-based system suitable for use in large networks.

What's more...

To complete the WLAN portfolio, LANCOM also offers suitable AirLancer client adapters and a large selection of high-end antennas for professional indoor and outdoor applications.

LANCOM XAP-40-2

Firewall	
Stateful inspection firewall	Direction-dependant check based on connection information
Packet filter	Check based on the header information of an IP packet (IP or MAC source/destination addresses; source/destination ports, DiffServ attribute); remote-site dependant, direction dependant, bandwidth dependant
Masquerading	Network Address Translation (NAT), N:N mapping for the translation or masking of IP addresses
Port mapping	Provision of services from behind masqueraded computers, for example, to make an internal web server available from the outside (inverse masquerading)
Tagging	The firewall marks packets with routing tags, e.g. for policy-based routing
Actions	Forward, drop, reject, block sender address, close destination port, disconnect
Messaging	Via e-mail, SYSLOG or SNMP trap
Quality of Service	
Traffic shaping	Dynamic bandwidth management with IP traffic shaping
Bandwidth reservation	Dynamic reservation of minimum and maximum bandwidths, absolute or connection-related, separate settings for send and receive directions
DiffServ/TOS	Priority packet queuing based on DiffServ/TOS fields
Packet-size control	Automatic packet-size control by fragmentation or Path Maximum Transmission Unit (PMTU) adjustment.
Layer 2/Layer 3 tagging	Automatic or fixed translation of layer-2 priority information (802.11p-marked Ethernet frames) to layer-3 DiffServ attributes in routing mode. Translation from layer 3 to layer 2 with automatic recognition of 802.1p-support in the destination device.
Security	
Intrusion Prevention	Monitoring and blockage of login attempts and port scans
IP spoofing	Source IP address check on all interfaces: The only accepted IP addresses belong to the previously defined IP network
Access Control lists	Filtering of IP or MAC addresses and preset protocols for configuration access and LANCAPI
Denial of Service protection	Protection from fragmentation errors and SYN flooding
General	Detailed settings for handling reassembly, PING, stealth mode and AUTH port
URL blocker	Filtering of unwanted URLs based on DNS hitlists and wildcard filters
Password protection	Password-protected configuration access can be set for each interface
Alerts	Alerts via e-mail, SNMP-Traps and SYSLOG
Authentication mechanisms	PAP, CHAP and MS-CHAP as PPP authentication mechanism
High availability / redundancy	
VRRP	VRRP (Virtual Router Redundancy Protocol) for non-proprietary backup in case of failure of a device or remote station. Enables passive standby groups or reciprocal backup between multiple active devices including load balancing and freely definable backup priorities
FirmSafe	For completely safe software upgrades thanks to two stored firmware versions, incl. test mode for firmware updates
Analog/GSM modem backup	Optional operation of an analog or GSM modem at the serial interface
Line monitoring	Line monitoring with LCP echo monitoring, up to 4 addresses for end-to-end monitoring with ICMP polling.
WLAN	
Frequency band 2.4 GHz and 5 GHz (EU version)	2400 - 2483.5 MHz (ISM) and 5150-5750 or 5725-5825 MHz (UK only)
Transfer rates 2.4 GHz	54 Mbps to IEEE 802.11g (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection) compatible to IEEE 802.11b (11, 5.5, 2, 1 Mbps, Automatic Rate Selection), 802.11 b/g compatibility mode or pure g or pure b, Super A/G with Turbo Mode (108Mbps), bursting, compression
Transfer rates 5 GHz	54 Mbps to IEEE 802.11a/h (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), Super A/G with Turbo Mode (108Mbps), bursting, compression, fully compatible with TPC (adjustable power output) and DFS (automatic channel selection, radar detection) according to ETSI regulations
Range *	Up to 150 m (up to 30 m in buildings) *
Maximum transmission power 2.4 GHz	802.11b: +19dBm @ 1 and 2Mbps, +19dBm @ 5.5 and 11Mbps
Maximum transmission power 2.4 GHz	802.11g: +19dBm @ 6Mbps, +14dBm @ 54Mbps
Maximum transmission power 5 GHz	802.11a/h: +18dBm @ 6Mbps, +12dBm @ 54Mbps with automatic transmission power control (TPC) and manual power settings
Minimum transmission power	Transmission-power reduction in software by 1dB steps to min. 0.5 dBm
Reception sensitivity 2.4 GHz	802.11b: -87dBm @ 11Mbps, -94dBm @ 1Mbps
Reception sensitivity 2.4 GHz	802.11g: -87dBm @ 6Mbps, -70dBm @ 54Mbps
Reception sensitivity 5 GHz	802.11a/h: -87dBm @ 6Mbps, -67dBm @ 54Mbps

LANCOM XAP-40-2

WLAN	
Radio channels 2.4 GHz	Up to 13 channels, max. 3 non-overlapping (2.4-GHz band)
Radio channels 5 GHz	Up to 19 non-overlapping channels (5 GHz band) with automatic dynamic channel selection (DFS)
Roaming	Seamless handover between radio cells, IAPP support, IEEE 802.11d support
WPA2 fast roaming	Pre-authentication and PMK caching for fast 802.1x authentication
Fast client roaming	With background scanning, mobile access points in client mode can switch to alternative access points which offer a better signal before the connection to the first access point fails
VLAN	Support of up to 4094 VLAN IDs for WLAN connections, 32 simultaneously usable VLAN tags for 802.11x clients
Multi SSID	Simultaneous use of up to 8 independent WLAN networks per WLAN interface
Security	IEEE 802.11i / WPA2 with passphrase or 802.1x and hardware-accelerated AES, closed network, WEP64, WEP128, WEP152, access control lists, RADIUS client, user authentication, 802.1x /EAP
RADIUS server	Integrated RADIUS server for MAC address list management
Quality of Service	Support of Wireless Multimedia Extensions (WME, integral to IEEE802.11e), for example for prioritization of voice clients
Bandwidth limitation	Each WLAN client (MAC address) can be assigned maximum transmit and receive rates and an individual VLAN ID
Background scanning	The detection of rogue access points and the channel properties is carried out almost unnoticeably for all WLAN channels during normal AP operation.
Client detection	Rogue WLAN client detection based on probe requests
802.1x supplicant	Authentication of an access point in WLAN client mode at another access point via 802.1X (EAP-TLS, EAP-TTLS and PEAP)
Notice	* The effective distance and transmission rate that can be achieved are depending of the given building conditions.
WLAN operating modes	
WLAN access point	Infrastructure mode
WLAN bridge	Point-to-multipoint connection of up to 7 Ethernet LANs (mixed operation optional), broken link detection, blind mode, up to 32 VLANs simultaneously for WLAN connections
WLAN router	Use of the LAN connector for simultaneous DSL over LAN, IP router, NAT/Reverse NAT (IP masquerading) DHCP server, DHCP client, DHCP relay server, DNS server, PPPoE client (incl. Multi-PPPoE), PPTP client and server, NetBIOS proxy, DynDNS client, NTP, port mapping, policy-based routing based on routing tags, tagging based on firewall rules, dynamic routing with RIPv2, VRRP, spanning-tree protocol to support redundant routes in Ethernet networks
WLAN client	Transparent WLAN client node for wireless Ethernet extensions, e.g. connecting PCs or printers by Ethernet; up to 64 MAC addresses
Routing functions	
Router	IP and NetBIOS/IP multi-protocol router
HTTP	HTTP and HTTPS server for configuration by web interface
DNS	DNS client, DNS server, DNS relay, DNS proxy and dynamic DNS client
DHCP	DHCP client, DHCP relay and DHCP server with autodetection
NetBIOS	NetBIOS/IP proxy
NTP	NTP client and SNTP server, automatic adjustment for daylight-saving time
Policy-based routing	Policy-based routing based on routing tags. Based on firewall rules, certain data types are marked for specific routing, e.g. to particular remote sites or lines.
Dynamic routing	Dynamic routing with RIPv2. Learning and propagating routes; separate settings for LAN and WAN
LAN protocols	
IP	ARP, proxy ARP, BOOTP, LANCAP, DHCP, DNS, HTTP, HTTPS, IP, ICMP, NTP/SNTP, NetBIOS, PPPoE (server), RADIUS, RIP-1, RIP-2, RTP, SIP, SNMP, TCP, TFTP, UDP, VRRP
WLAN protocols	
Ethernet	PPPoE, Multi-PPPoE, ML-PPP, PPTP (PAC or PNS) and plain Ethernet (with or without DHCP), RIP-1, RIP-2
Interfaces	
LAN	10/100Base-TX, autosensing, auto node hub, PoE compliant with IEEE 802.3af
2nd LAN port	10/100Base-TX, autosensing, auto node hub, PoE compliant with IEEE 802.3af
Serial interface	Serial configuration interface / COM port (8 pin Mini-DIN): 9,600 - 115,000 baud, suitable for optional connection of analog/GPRS modems
External antenna connectors	Four reverse SMA connectors for external LANCOM AirLancer Extender antennas or for antennas from other vendors. Please respect the restrictions which apply in your country when setting up an antenna system. For information about calculating the correct antenna setup, please refer to www.lancom-systems.com .

LANCOM XAP-40-2

Management	
LANconfig	Configuration program for Microsoft Windows, incl. convenient Setup Wizards. Optional group configuration, simultaneous remote configuration and management of multiple devices over IP connection (HTTPS, HTTP, TFTP)
LANmonitor	Monitoring application for Microsoft Windows for (remote) surveillance and logging of the status of LANCOM devices and connections, incl. PING diagnosis
WLANmonitor	Monitoring application for Microsoft Windows for the visualization and monitoring of LANCOM WLAN installations, incl. Rogue AP and Rogue Client visualization
Webconfig	Integrated web server for the configuration of LANCOM devices via Internet browsers with HTTPS or HTTP
Access rights	Individual access and function rights for up to 16 administrators
User administration	RADIUS user administration for dial-in access (PPP/PPTP and ISDN CLIP)
Remote maintenance	Remote configuration with Telnet/SSL, SSH (with password or certificate), browser (HTTP/HTTPS), TFTP or SNMP, firmware upload via HTTP/HTTPS or TFTP
Security	Access rights (read/Write) over WAN, LAN or WLAN can be set up separately (VPN only, Telnet/SSL, SSH, SNMP, HTTPS/HTTP), access control list
Scripting	Scripting function for batch-programming of all command-line parameters and for transferring (partial) configurations, irrespective of software versions and device types, incl. test mode for parameter changes
SNMP	SNMP management via SNMP V2, private MIB exportable by WEBconfig, MIB II
Timed control	Scheduled control of parameters and actions (e.g. firewall rules or connection establishment) with CRON service
TFTP	TFTP client and server with variable file names (name, MAC/IP address, serial number)
Diagnosis	Extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, LANmonitor status display, internal logging buffer for SYSLOG and firewall events, monitor mode for Ethernet ports
AirWave	Supported by the LANCOM Enterprise Management System (AirWave AMP, Site Planner, RAPIDS, Client)
Statistics	
Statistics	Extensive Ethernet, IP and DNS statistics; SYSLOG error counter
Accounting	Connection time, online time, transfer volumes per station. Snapshot function for regular read-out of values at the end of a billing period.
Export	Accounting information exportable via LANmonitor and SYSLOG
Hardware	
Power supply	12 V DC, external power adapter (230 V)
Power supply	Via Power over Ethernet compliant with IEEE802.3af
Power supply	2 x 24V DC, redundant
Environment	Temperature range -20 – +50 °humidity 0-95 %; non-condensing
Housing	Robust metal housing, connections on the front of the device; measurements 80x100x135 mm (WxHxD), ready for wall and top-hat rail mounting
Power consumption (max)	ca. 10 Watts
Declarations of conformity	
CE	EN 55022, EN 301 489-1, EN 301 489-17, EN 60950
2.4 GHz WLAN	ETS 300 328
5 GHz WLAN	EN 301 893
Industrial	EN 61000-6-2: Electromagnetic compability, Immunity for industrial environments
Programmable Controllers	EN 61131-2: 2003 Part 2: Equipment requirements and tests (Chapter 6.1.1; 6.1.2 (+5°- +55°6.3.1.1; 6.3.2; 6.3.3.1; 8.2; 8.3 (Zone B); 9.11; 9.12)
Railway Applications	EN 50155: 2001 + A1:2002 + Corrigendum 2003, Electronic Equipment used on rolling stock (Chapter 10.2.2; only AC mains power; 10.2.3; 10.2.4; 10.2.6.1; 10.2.6.2; 10.2.6.4; 10.2.7; 10.2.8; 10.2.9.1; 10.2.11)
Vehicles	Commission Directive 2006/28/EC of 6 March 2006, radio interference (electromagnetic compatibility) of vehicles
Notifications	Certifications notified in Germany, Belgium, Netherlands, Luxembourg, Austria, Switzerland, UK, Italy, Spain, France, Portugal
Package content	
Manual	Printed User Manual (DE, EN) and Quick Installation Guide (DE/EN/FR/ES/IT/PT/NL)
CD	CD with firmware, management software (LANconfig, LANmonitor, LANCAPI) and documentation
Cable	Serial configuration cable, 1.5m
Cable	1 Ethernet cable, 3m
Antennas	Two 3-dBi dipole dualband antennas
Power supply unit	12 V DC, external power adapter (230 V)

LANCOM XAP-40-2

Support	
Warranty	3 years, support via Hotline and Internet KnowledgeBase
Software updates	Regular free updates (LCOS operating system and management tools) via Internet
Options	
Options	LANCOM Service Option (24h advance replacement within Germany, 4 year warranty, not for PoE Power Injector), item no. 61401
Options	LANCOM Public Spot Option (authentication and accounting software for hotspots), item no. 60642
Accessories	
External antennas	AirLancer Extender O-30 2.4 GHz outdoor antenna, item no. 60478
External antennas	AirLancer Extender O-70 2.4 GHz outdoor antenna, item no. 60469
External antennas	AirLancer Extender O-9a 5 GHz outdoor antenna, item no. 61220
External antennas	AirLancer Extender O-18a 5 GHz outdoor antenna, item no. 61210
External antennas	AirLancer Extender O-D80g 2.4 GHz polarization diversity outdoor sector antenna, item no. 61221
External antennas	AirLancer Extender O-D60a 5 GHz polarization diversity outdoor sector antenna, item no. 61222
External antennas	AirLancer Extender O-360ag dualband omnidirectional outdoor antenna, item no. 61223
External antennas	AirLancer Extender I-60ag dualband indoor sector antenna, item no. 61214
External antennas	AirLancer Extender I-180 omnidirectional 2.4 GHz indoor antenna, item no. 60914
External antennas	AirLancer Extender I-360 omnidirectional 2.4 GHz indoor antenna, item no. 00745
Antenna cable	AirLancer cable NJ-NP 3m antenna-cable extension, item no. 61230
Antenna cable	AirLancer cable NJ-NP 6m antenna-cable extension, item no. 61231
Antenna cable	AirLancer cable NJ-NP 9m antenna-cable extension, item no. 61232
Lightning Protection (antenna cable)	AirLancer Extender SA-5 lightning protection (2.4 and 5 GHz), item no. 61212
Lightning Protection (LAN cable)	AirLancer Extender SA-LAN lightning protection LAN cable, item no. 61213
Documentation	LANCOM LCOS Reference Manual (DE), item no. 61700
Power over Ethernet	LANCOM PoE Power Injector, item no. 61502
Item numbers	
LANCOM XAP-40-2	61147
LANCOM XAP-40-2	61147

LANCOM, LANCOM Systems and LCOS are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. Subject to change without notice. No liability for technical errors and/or omissions. 12/06